

MAXXUM ROPS

CASE IH
AGRICULTURE
THE HEART OF FARMING BEATS RED



The Case IH Maxxum ROPS is available in two sizes; the four cylinder 110 and the six cylinder 125.

These popular tractors combine the great features & strength of the legendary Case IH Maxxum with the ease of access of a ROPS tractor. Maxxum ROPS is ideal for dairy operations in our region. The Maxxum is also available with a cab and is one of our most popular tractors.

MAXXUM 110 ROPS SPECIFICATIONS

Engine	FPT NEF 4.5 litre, 4 cyl, turbo, mechanical injection, Tier 3	
Rated power @ 2200 rpm	ECE R120	107 hp
Max Torque @ 1,250 rpm	455 Nm	
Fuel Tank	176 litres* with guard	
Transmission	40km/h 16x16 semi powershift, power-synchro shuttle	
Front Axle	Class 3, 4WD, limited slip diff, 55° Steering angle	
Rear Axle	330331	HD Flange with diff lock, IAR 1:1.353
Brakes	Extended life multi-disc in rear axle	
Hydraulics	334844	64 l/min fixed display, pump with 3 mech, rear remotes
Linkage	330970	MDC, max capacity: 5,682kg, 1 int. + 2 external rams Cat 2 hook ends
PTO	330801	540, 540E & 1000 with 6 x 21 spline shafts
Electric System	12v, 120 amp alternator, 1x 107ah battery	
Cab	ROPS with canopy, RH and LH steps, mirrors	
Work lights	330925	2 rear on ROPS frame
Frame	330217	Narrow rear fenders, dynamic front fenders
Ballast	Front weight carrier with 6 weight pack	
Wheelbase	2,412 mm*	
Minimum shipping weight	4,500 kg*	
Wheels	540/65/R38 & 440/65/R28	

MAXXUM 125 ROPS SPECIFICATIONS

Engine	FPT NEF 6.7 litre, 6 cyl, turbo, Mmechanical injection, Tier 3	
Rated power @ 2200 rpm	ECE R120	126 hp
Max Torque @ 1,250 rpm	560 Nm	
Fuel Tank	250 litres with guard	
Transmission	40km/h 16x16 semi powershift, power-synchro shuttle	
Front Axle	Class 3, 4WD, limited slip diff, 55° Steering angle	
Rear Axle	Flange axle with diff lock, IAR 1:1.353	
Hydraulics	334844	113 l/min with CCLS with 3 mech, rear remotes (2 configurable)
Linkage	330970	MHC, max capacity: 5,628kg, with Cat 2 hook ends
PTO	330801	540, 540E & 1000 with 6 x 21 spline shafts
Electric System	12v, 120 amp alternator, 1x 107ah battery	
Cab	ROPS with canopy, RH and LH steps, mirrors	
Work lights	330925	2 rear on ROPS frame
Frame	330217	Narrow rear fenders, dynamic front fenders
Ballast	Wide front weight carrier — no weights	
Wheelbase	2,652 mm	
Minimum shipping weight	Approx 4,700 kg	
Wheels	650/60/R38 & 520/60/R28 or 600/65/R38 & 480/65/R28	
	* approximate size	



3 Year/3000 Hour Warranty

We recognise you expect your product will deliver on the ever increasing productivity demands. Case IH customers deserve the additional peace of mind of knowing your product is covered should the unexpected occur with 3 years/ 3000 hour standard REDCover Plus Protection Plan.

CAMBRIDGE
183 Victoria Road
07 827 7159

OTOROHANGA
1 Progress Drive
07 873 4004

ROTORUA
22 Fairy Springs Road
07 343 1915

www.gaz.co.nz

Giltrap AgriZone
Keeping Agriculture Moving